

pyFBS: A Python package for Frequency Based Substructuring

Tomaž Bregar¹, Ahmed El Mahmoudi², Miha Kodrič³, Domen Ocepek³, Francesco Trainotti², Miha Pogačar³, Mert Gödeli², Gregor Čepon³, Miha Boltežar³, and Daniel J. Rixen²

¹ Gorenje d.o.o., Partizanska 12, 3503 Velenje, Slovenia ² Technical University of Munich, Institute of Applied Mechanics, Boltzmannstr. 15, 85748 Garching, Germany ³ Faculty of Mechanical Engineering, University of Ljubljana, Aškerčeva 6, 1000 Ljubljana, Slovenia

DOI: [10.21105/joss.03399](https://doi.org/10.21105/joss.03399)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Kyle Niemeyer](#) ↗

Reviewers:

- [@ngoiz](#)
- [@LolloCappo](#)
- [@Gunnstein](#)

Submitted: 19 August 2020

Published: 19 January 2022

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

In science, engineering and technology complex problems are often decomposed into smaller, simpler subsystems. Each subsystem can then be analyzed and evaluated separately. This approach can often reduce the complexity of the overall problem and provide invaluable insight into the optimization and troubleshooting of each individual component. The subsystems can also be assembled back together and with that the system can be analyzed as a whole.

Dynamic Substructuring (DS) is an engineering concept where dynamic systems are modeled and analyzed in terms of their components or so-called substructures. There are several ways of formulating the dynamics of substructures. One of them is with Frequency Response Functions (FRFs), which describe the response as the result of a unit harmonic force. The method is well suited for experimental approaches where FRFs are obtained from measurement of components. Such approaches were already investigated in the 1970s ([Klosterman, 1971](#)) and 1980s ([Crowley et al., 1984](#); [Jetmundsen et al., 1988](#); [Martinez et al., 1984](#); [Urgueira, 1989](#)). Due to complicated formulations and difficulties in obtaining good measurements, the method was hardly applicable. Thanks to better measurement hardware and proper formulation of the problem, Frequency Based Substructuring (FBS) has gained popularity in recent years ([Klerk, Rixen, & Voormeeren, 2008](#); [Rixen et al., 2006](#); [Seijs et al., 2016](#)). With this approach, it is also possible to build hybrid models in which experimentally characterized and numerically modelled parts are combined.

pyFBS is a Python package for Frequency Based Substructuring. The package implements an object-oriented approach for dynamic substructuring. Current state-of-the-art methodologies in frequency based substructuring are available in pyFBS. Each method can be used as a standalone or interchangeably with others. Also a 3D display is available so a user can simply place and orient associated input/outputs used with each method. Furthermore, basic and application examples are provided with the package together with real experimental and numerical data ([El Mahmoudi et al., 2019](#)).

Statement of need

Evaluating structural dynamics is a necessary step in the development of any complex mechanical system. Vibro-acoustic character together with the visual design contributes to the customer's perception of a premium product. With DS the vibro-acoustic performance of a product can be analysed in terms of its subcomponents. This approach is highly beneficial,

as almost all complex products are designed modularly. pyFBS helps the user to perform experimental modelling in DS. It enables an intuitive way to position sensors and impact locations on the analysed structures. The position and orientation of sensors/impacts can be then be used in each implemented DS method. Furthermore, experimental measurements can be simulated with ease from a numerical model, where the same positional information can be used.

To the best of authors knowledge there is currently no open source software alternative, which would enable the user to use dynamic substructuring methodologies. pyFBS has been designed to be used for scientific research in the field of dynamic substructuring. It is currently being used by a number of undergraduate students and postgraduate researchers.

Features

pyFBS enables the user to use state-of-the-art dynamic substructuring methodologies in an intuitive manner. Currently implemented features are listed below.

3D display

Structures and positions of impacts, sensors and channels can be visualized in 3D in [Figure 1](#). The 3D display is built on top of PyVista ([Sullivan & Kaszynski, 2019](#)) and enables an intuitive way to display relevant data. Sensors and impacts can be interactively positioned on structures and the updated positions can be directly used within the pyFBS. With this feature the experimental setup can be prepared in advance, to avoid possible mistakes in experimental modelling. Furthermore, various animations can be performed directly in the 3D display, such as the animation of mode shapes or operational deflection shapes.




Figure 1: An example of a simple structure depicted in the pyFBS 3D display.

FRF synthetization

Frequency Response Functions can be synthesized for predefined positions of channels and impacts in a numerical model. Currently, mode superposition FRF synthetization is supported,

where mass and stiffness matrices are imported from FEM software. Damping can be introduced as modal damping for each mode shape. Additionally, noise can be introduced to the response so a realistic set of FRFs, representing experimental measurements, can be obtained.

Virtual Point Transformation (VPT)

VPT projects measured dynamics on the predefined interface displacement modes (IDMs) (Klerk, Rixen, Voormeeren, & Pasteuning, 2008). The interface is usually considered to be rigid; therefore, only 6 rigid IDMs are used in the transformation. After applying the transformation, a collocated set of FRFs is obtained, which can afterwards directly be used in DS. Expanded VPT is also supported, where directly measured rotational response is included in the transformation (Bregar et al., 2020).

System Equivalent Model Mixing (SEMM)

SEMM enables mixing of two equivalent frequency-based models into a hybrid model (Klaassen et al., 2018; Klaassen & Rixen, 2020). The models used can either be of numerical or experimental nature. One of the models provides the dynamic properties (overlay model) and the second model provides a set of degrees of freedom. A numerical model is commonly used as a parent model and an experimental model is used as an overlay model.

Discussion

The development of the pyFBS is an ongoing effort. Currently the package is used as a research tool. In the future, more examples on the topic of DS and applications of Transfer Path Analysis (TPA) are going to be introduced in the documentation. Furthermore, implementation of Operational Source Identification (OSI) is going to be integrated into the pyFBS in the near future.

Acknowledgments

The pyFBS package was developed as a part of collaboration between the Laboratory for Dynamics of Machines and Structures (LADISK), Faculty of Mechanical Engineering, University of Ljubljana (UL FME) and the Chair of Applied Mechanics (AM), Technical University of Munich (TUM).

References

- Bregar, T., Holeček, N., Čepon, G., Rixen, D. J., & Boltežar, M. (2020). Including directly measured rotations in the virtual point transformation. *Mechanical Systems and Signal Processing*, 141, 106440. <https://doi.org/10.1016/j.ymssp.2019.106440>
- Crowley, J. R., Klosterman, A. L., Rocklin, G. T., & Vold, H. (1984). Direct structural modification using frequency response functions. *Proceedings of IMAC II*.
- El Mahmoudi, A., Trainotti, F., Park, K., & Rixen, D. J. (2019, November 26). In-situ TPA for NVH analysis of powertrains: An evaluation on an experimental test setup. *AAC 2019 : Aachen Acoustics Colloquium/Aachener Akustik Kolloquium*.

- Jetmundsen, B., Bielawa, R. L., & Flannelly, W. G. (1988). Generalized frequency domain substructure synthesis. *Jnl. American Helicopter Society*, 33(1), 55–64.
- Klaassen, S. W., & Rixen, D. J. (2020). The Inclusion of a Singular-value Based Filter in SEMM. In: *Proceedings of the 38th International Modal Analysis Conference, A Conference on Structural Dynamics*, (2020).
- Klaassen, S. W., Seijs, M. V. van der, & Klerk, D. de. (2018). System equivalent model mixing. *Mechanical Systems and Signal Processing*, 105, 90–112. <https://doi.org/10.1016/j.ymssp.2017.12.003>
- Klerk, D. de, Rixen, D. J., & Voormeeren, S. N. (2008). General framework for dynamic substructuring: History, review and classification of techniques. *AIAA Journal*, 46(5), 1169–1181. <https://doi.org/10.2514/1.33274>
- Klerk, D. de, Rixen, D. J., Voormeeren, S. N., & Pasteuning, F. (2008). Solving the RDoF Problem in Experimental Dynamic Substructuring. In: *Proceedings of the 26th International Modal Analysis Conference, A Conference on Structural Dynamics*, (2010).
- Klosterman, A. L. (1971). *A combined experimental and analytical procedure for improving automotive system dynamics* [PhD thesis, University of Cincinnati, Department of Mechanical Engineering]. <https://doi.org/10.4271/720093>
- Martinez, D. R., Carrie, T. G., Gregory, D. L., & Miller, A. K. (1984). Combined Experimental/Analytical Modelling using component modes synthesis. *25th Structures, Structural Dynamics and Materials Conference*, 140–152. <https://doi.org/10.2514/6.1984-941>
- Rixen, D. J., Godeby, T., & Pagnacco, E. (2006). Dual assembly of substructures and the FBS method: Application to the dynamic testing of a guitar. *International Conference on Noise and Vibration Engineering, ISMA*.
- Seijs, M. V. van der, Klerk, D. de, & Rixen, D. J. (2016). General framework for transfer path analysis: History, theory and classification of techniques. *Mechanical Systems and Signal Processing*, 68–69, 217–244. <https://doi.org/10.1016/j.ymssp.2015.08.004>
- Sullivan, C. B., & Kaszynski, A. (2019). PyVista: 3D plotting and mesh analysis through a streamlined interface for the visualization toolkit (VTK). *Journal of Open Source Software*, 4(37), 1450. <https://doi.org/10.21105/joss.01450>
- Urgueira, A. P. V. (1989). *Dynamic analysis of coupled structures using experimental data* [PhD thesis]. Imperial College.